

6708

FPS File Copy  
AFTAC Project No. VELA T/6708  
ARPA Order No. 624  
ARPA Program Code No. 6F10

Distribution of this document  
is unlimited

(1)  
WB

BATHYMETRY PROGRAM  
KURILE ISLANDS EXPERIMENT

Special Report No. 3  
OCEAN-BOTTOM SEISMOGRAPHIC EXPERIMENTS

Prepared by  
R. F. Howard

Ralph R. Guidroz, Program Manager  
Telephone: 1-214-357-5411, Ext. 447

TEXAS INSTRUMENTS INCORPORATED  
Science Services Division  
P.O. Box 5621  
Dallas, Texas 75222

28 April 1967

DDC  
OCT 27 1970  
RECEIVED  
D  
LB

ACKNOWLEDGMENT

This research was supported by the  
ADVANCED RESEARCH PROJECTS AGENCY,  
Nuclear Test Detection Office,  
under Project VELA UNIFORM,  
and accomplished under the technical direction of the  
AIR FORCE TECHNICAL APPLICATIONS CENTER,  
Contract No. F 33657-67-C-0105

Effective Date of Contract: 28 July 1966  
Contract Expiration Date: 27 April 1967  
Amount of Contract: \$892,217

AD713126

**BEST  
AVAILABLE COPY**

AFTAC Project No. VELA T/6708  
ARPA Order No. 624  
ARPA Program Code No. 6F10

Distribution of this document  
is unlimited

**BATHYMETRY PROGRAM  
KURILE ISLANDS EXPERIMENT**

**Special Report No. 3  
OCEAN-BOTTOM SEISMOGRAPHIC EXPERIMENTS**

**Prepared by  
R. F. Howard**

**Ralph R. Guidroz, Program Manager  
Telephone: 1-214-357-5411, Ext. 447**

**TEXAS INSTRUMENTS INCORPORATED  
Science Services Division  
P.O. Box 5621  
Dallas, Texas 75222**

**28 April 1967**

This document has been approved  
for public release and sale; its  
distribution is unlimited.

**ACKNOWLEDGMENT**

**This research was supported by the  
ADVANCED RESEARCH PROJECTS AGENCY,  
Nuclear Test Detection Office,  
under Project VELA UNIFORM,  
and accomplished under the technical direction of the  
AIR FORCE TECHNICAL APPLICATIONS CENTER,  
Contract No. F 33657-67-C-0105**

**DDC  
OCT 27 1970  
RECEIVED**

**Effective Date of Contract: 28 July 1966  
Contract Expiration Date: 27 April 1967  
Amount of Contract: \$892,217**



## ABSTRACT

A bathymetric survey was conducted as a part of the Kurile Islands Experiment (Ocean-Bottom Seismograph Experiments, Contract No. F 33657-67-C-0105). Since the primary efforts of the experiment were directed toward the Ocean-Bottom Seismograph and Explosive Program, the method used during the bathymetric survey was appropriate but not optimum. Bathymetric data were very good and were as reliable as navigation would permit. However, the profile coverage was generally too sparse. The conclusion is that observations of depth values, OBS-environmental relations and overall bathymetry are valid within navigational limits.



## TABLE OF CONTENTS

Section	Title	Page
I	INTRODUCTION	1
II	SUMMARY OF THE SURVEY	2
III	DATA ANALYSES	13
IV	CRITIQUE	17/18

## LIST OF ILLUSTRATIONS

Figure	Description	Page
1	Ocean Sonics, Inc. GDR-T Fathometer	2
2	Event, System and Depth Profile Chart	3/4
3	Bathymetry of the Kurile Area	7/8
4	Bathymetric Profiles, Kurile Area	11/12

## LIST OF TABLES

Table	Title	Page
1	Position and Depth Reliability	9/10



---

## **BATHYMETRY PROGRAM KURILE ISLANDS EXPERIMENT**

### **SECTION I INTRODUCTION**

An Ocean-Bottom Seismograph experiment which investigated the seismicity of the area and evaluated the operational worthiness of the instrument, was conducted near the Kurile Islands during the fall of 1966. An explosive program was used to calibrate the instruments and to supplement natural seismicity. To aid in evaluating data, a bathymetric survey was conducted, with profile coverage controlled by Ocean-Bottom Seismometer and Explosive Program operations.

The objectives of this report are to explain observations made during current Kurile bathymetric analysis and to help formulate new ideas or substantiate old ones in interpretation of Kurile Arc geology.



## SECTION II

### SUMMARY OF THE SURVEY

The M/V Campeche Seal and M/V Pacific Seal were each equipped with an Ocean Sonics, Inc. GDR-T fathometer (Figure 1). Sounding records were obtained for 24 profiles in an area approximately 420 mi long and 250 mi wide from the northern tip of Hokkaido, Japan, northeast to Shasukotan Island of the Kurile Islands chain. Profile coverage was determined from OBS drop and recovery sights and explosion locations (Figure 2). Fathometer malfunction on the M/V Pacific Seal eliminated data collection in the near-island waters. The M/V Campeche Seal collected all 24 profiles; 11 traverse the trench and 16 traverse the shelf margin.




Figure 1. Ocean Sonics, Inc., GDR-T Fathometer


EVENT, SYSTEM, AND DEPTH PROFILE CHART

KURILE ISLANDS  
NORTH PACIFIC OCEAN

MERCATOR PROJECTION  
SCALE: Based on Lat. 52° 30'

LEGEND:

- EVENT LOCATION      ◻ UNRECOVERED SYSTEM  
● SYSTEM LOCATION    PL DEPTH PROFILE



A






Figure 2. Event, System and Depth Profile Chart



Navigation was primarily controlled by dead-reckoning and celestial techniques including star fixes and sun lines and had an estimated 2- to 5-mi accuracy. Approximate positions for dead-reckoning were validated using the nearest reliable fix while taking into consideration weather conditions.

Depth-value interpretation was accurate to 20 fm  $\pm$  navigational error with fathometer depths at event locations checked by computing travel-time data recorded with a marine geophone. Such a navigational error was indicated by the erratic values for computed depth readings of 98 fm above to 192 fm below the fathometer depths. Depth values (underlined in Figure 3) from previous surveys agreed with current data and were used to control the dashed contours which were used in areas this survey did not cover, including instrument positions not visited by M/V Campeche Seal. Instrument positions sounded (stations 5, 7, 9, 11, 12, 13, and 10; Figure 2) had depth accuracies based on navigation limits; however, actual instrument depths and geographical locations on the ocean bottom have not been validated. Table 1 gives depth-position reliability for those points indicated on profiles in Figure 4.

Two areas of comparatively reliable position and depth accuracy, due to better profile coverage, occur near 44°00'N, 149°30'E and 46°30'N, 153°00'E.

**BATHYMETRY OF THE KURILE AREA**

**KURILE ISLANDS  
NORTH PACIFIC OCEAN**


**MERCATOR PROJECTION**

**SCALE: Based on Lat. 52° 30'**

**LEGEND:**

**CONTOUR INTERVAL—200 FATHOMS**

**—○— TRENCH AXIS**



A




Figure 3. Bathymetry of the Kurile Area

B




**Table 1**  
**POSITION AND DEPTH RELIABILITY**

Profile	Total Profile Rel.	Position A			Position B			Position C			Position D		
		Lat. Long.	Rel. (mi)	Depth (fm)	Lat. Long.	Rel. (mi)	Depth (fm)	Lat. Long.	Rel. (mi)	Depth (fm)	Lat. Long.	Rel. (mi)	Depth (fm)
1	Very Good	43°00' 144°22' ●●	± 1	3.8	42°55' 145°00' ●	± 1	520.0	43°05' 146°46' ○	± 2	1480.0	43°06' 148°00' ●	± 2	2130.0
3	Good	43°34' 148°20' ○	± 3	2300.0	43°27' 148°30' ○	± 3	3165.0	43°21' 148°41' ○	± 4	4695.0	43°09' 148°58' ○	± 5	2865.0
4	Good	43°01' 149°12' ●	± 3	3185.0	43°32' 149°11' ○	± 4	4885.0	43°47' 149°12' ○	± 5	2920.0	44°11' 149°18' ○	± 3	2210.0
5	Good	44°00' 149°20' ○	± 3	3018.0	44°05' 149°12' ○	± 4	2300.0	44°23' 148°58' ○	± 4	2300.0	-	-	-
6	Fair	44°23' 148°58' ○	± 4	2300.0	44°22' 149°18' ○	± 4	2330.0	44°23' 150°37' ○	± 3	3900.0	44°23' 151°09' ●	± 2	4620.0
7	Good	44°31' 151°15' ○	± 2	4500.0	44°20' 151°20' ○	± 3	3845.0	43°59' 151°36' ○	± 3	2890.0	43°35' 152°00' ○	± 3	2690.0
8	Good	43°31' 151°57' ○	± 3	2660.0	44°07' 151°57' ○	± 3	3285.0	44°52' 152°02' ○	± 3	4300.0	45°37' 152°02' ●○	± 2	2140.0
9	Fair	45°37' 152°06' ○	± 2	2360.0	46°02' 152°40' ○	± 3	2985.0	46°13' 152°49' ○	± 3	1960.0	46°19' 152°58' ○	± 3	2215.0
10	Poor	46°20' 153°01' ○	± 4	2100.0	46°14' 153°13' ○	± 4	2270.0	46°06' 153°29' ○	± 4	3025.0	46°01' 153°41' ○	± 4	3310.0
12	Very Good	46°24' 153°04' ●	± 2	1940.0	46°40' 153°26' ○	± 3	1760.0	46°48' 153°38' ○	± 3	1720.0	46°59' 153°54' ●	± 2	1800.0
13	Good	47°04' 153°54' ●○	± 2	1900.0	46°46' 154°33' ○	± 3	3700.0	46°34' 154°58' ○	± 4	3180.0	46°28' 155°11' ○	± 5	2850.0
15	Good	47°39' 153°51' ○	± 3	1165.0	47°13' 154°16' ○	± 4	2480.0	46°54' 154°42' ○	± 4	4000.0	46°28' 155°11' ○	± 3	2850.0
16	Good	46°13' 152°29' ○	± 1	1520.0	46°22' 153°44' ●	± 2	2940.0	46°24' 154°57' ○	± 3	3225.0	46°26' 155°20' ○	± 4	2885.0
17	Fair	46°46' 154°14' ○	± 3	2670.0	46°40' 153°47' ○	± 3	1905.0	46°37' 153°32' ○	± 3	1490.0	46°31' 153°07' ○	± 4	1670.0
18	Fair	46°33' 153°12' ○	± 4	2365.0	45°54' 153°12' ○	± 4	4030.0	46°20' 153°12' ○	± 4	3800.0	45°00' 153°12' ●●	± 2	3150.0
19	Good	45°07' 150°48' ○	± 3	2610.0	45°06' 152°09' ●○	± 2	4650.0	45°00' 153°00' ○	± 3	3200.0	44°59' 153°07' ○	± 2	3180.0
20	Good	45°00' 150°32' ○	± 3	2135.0	44°45' 150°25' ●	± 3	2430.0	44°04' 149°55' ○	± 4	4340.0	43°45' 149°42' ●	± 2	4640.0
21	Fair	43°40' 149°40' ●○	± 2	4315.0	43°37' 149°18' ○	± 3	4920.0	43°31' 148°42' ○	± 4	3090.0	43°30' 148°24' ○	± 4	2080.0
22	Good	43°02' 150°25' ○●	± 1	2645.0	43°32' 149°52' ○	± 2	3460.0	43°39' 149°42' ○	± 2	4200.0	-	-	-
23	Good	43°41' 149°43' ●	± 1	4160.0	43°57' 149°32' ○	± 2	3905.0	44°19' 149°20' ○	± 2	3200.0	44°19' 149°20' ●○	± 3	2295.0
24	Very Good	41°15' 148°14' ●	± 1	3085.0	42°20' 150°40' ○	± 2	2365.0	43°02' 152°14' ●	± 1	2685.0	43°29' 152°05' ○●	± 3	2815.0


\* Reliability limits are estimates of position accuracy considering  
 ● Nearest reliable fix (celestial, Loren end/or radar)  
 ● Weather conditions during fix and voyage traverse  
 ● Length of dead-reckoning and speed of traverse  
 ● Combinations of any of the above

\*\*Soundings are uncorrected for velocity gradient and subject to correction within limits imposed by position accuracy.

● Star fix  
 ● Loren fix  
 ○ Radar  
 ● Dead-reckoning end sun line  
 ○ Dead-reckoning



A



**BATHYMETRIC PROFILES  
KURILE ARC**  
(VERTICAL EXAGGERATION 20:1)

Figure 4. Bathymetric Profiles — Kurile Area



### SECTION III

#### DATA ANALYSES

Bathymetric data analyses indicate the shelf, shelf margin, and slope areas of the Kurile Trench to be more complex than previously mapped. A submarine canyon, or valley, originating between Shimushiru Island and the Chirihoi Islands (profile 9, Figure 4) is the dominant feature of a valley and ridge complex consisting of a smaller valley entering the trench to the northeast and a shelf margin cut by several valley and ridge features (profiles 12 and 17). Southwest of the canyon, the shelf appears to be smooth and has a consistent dip down to the shelf margin. Soundings across the shelf margin (profiles 6, 8, 10, 13, 15, 16, and 20) indicate a leveed or ridged marginal area.

The continental slope varies in dip from  $4^{\circ}$  to  $10^{\circ}$ . Two secondary ridge or bench-like features appear at approximately 800-fm intervals down the otherwise smooth slope (profiles 15, 19, 20, and 21).

Measurements taken at the 4000-fm level indicate an average trench width of 20 mi, narrowing to approximately 3 mi on profile 15 and widening to 30 mi on profiles 8 and 18. This survey recorded a maximum depth of 4992 fm at  $43^{\circ}48'N$ ,  $149^{\circ}38'E$ . (Depths shown on the bathymetric chart, Figure 3, are uncorrected; i.e., the velocity of sound in water is assumed to be 4800 fps.)

A noticeable increase in slope and considerable narrowing occur in the last several hundred fathoms of trench depth. Above this area, a more gradual outer slope of  $2^{\circ}$  to  $3^{\circ}$  ends in a low rise leveling off on the abyssal plain. Two seamounts were sounded on profile 24, but the extent of these features was not determined due to poor profile coverage.





The following paragraphs describe the bathymetry of OBS

locations:

- Positions S1 and S1A (Figure 2) are on the gradual-sloping shelf region in 400 and 900 fm of water, respectively, approximately 20 mi from land. Depth comparisons at S3A-S3 and S7-S7A indicate a  $3^{\circ}$  to  $4^{\circ}$  dip for this region.
- Positions S4, S4A and S7A are at approximately 230, 230 and 330 fm in near-island waters not covered by this survey.
- Position S8 is approximately 20 mi from land, as are S4, S4A and S7A, but is at 1750 fm, which is much deeper. This position falls within the boundaries of the canyon seen in profile 9 (Figure 4). Unit 23, dropped at this position, was not recovered, possibly due to the canyon's rough topographic characteristics.
- Positions S11 and S13 are located at 1650 and 1320 fm, respectively, in the valley and ridge complex previously mentioned. S13 is on a gradual slope, while S11 appears to be on the marginal rim. Depth comparisons at positions S5 and S5A show a dip of  $2^{\circ}$  to  $3^{\circ}$  for the outer-slope area.



- Position S5 at 4370 fm was the deepest OBS position and is approximately 9 mi southwest of the trench axis. This area is relatively smooth and has a gradual slope offering minimum interference to OBS operations.
- Positions S9 at 3200 fm, S12 at 2850 fm, and S5A at 3100 fm (26, 23, and 35 mi, respectively, from the trench axis) are associated with similar bathymetry on the outer slope approaching the abyssal plain.
- Position S10 at 3000 fm was the most remote OBS from which data were obtained, being approximately 132 mi southeast of the trench axis. Unit 12 at position S6, 160 mi southwest of S10, at 2920 fm, was not recovered. Both positions were in the flat, relatively featureless abyssal-plain region.
- Position S2 remains poorly defined in bathymetry and seismicity due to the absence of bathymetric data and failure to recover the unit.

Of the 18 units launched, 13 recorded usable data from which more extensive studies related to bathymetry will be made. Continued improvement of depth and position accuracy will offer more reliable bathymetric interpretation of these data.



---

## SECTION IV

### CRITIQUE

The general objective of this phase of the experiment was to provide bathymetric data with sufficient accuracy and reliability to verify or support OBS data interpretation. Primary efforts of the experiment were directed toward the Ocean-Bottom Seismograph and Explosive Program operations, with bathymetry as a secondary objective. Therefore, the method was appropriate but not optimum for a bathymetric survey.

Bathymetric data were very good and were as reliable as navigation would permit. Generally, however, profile coverage was too sparse; two exceptions were in areas of greater OBS activity where profile orientation became the problem.

The conclusion is that observations of depth values, OBS-environmental relations and overall bathymetry are valid within navigational limits.

## DOCUMENT CONTROL DATA - R&amp;D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Texas Instruments Incorporated Science Services Division P. O. Box 5621 Dallas, Texas 75222		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP —	
3. REPORT TITLE  BATHYMETRY PROGRAM - KURILE ISLANDS EXPERIMENT SPECIAL REPORT NO. 3 OCEAN-BOTTOM SEISMOGRAPH EXPERIMENTS			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Special			
5. AUTHOR(S) (Last name, first name, initial)  Howard, R. F.			
6. REPORT DATE 28 April 1967		7a. TOTAL NO. OF PAGES 14	7b. NO. OF REFS 0
8a. CONTRACT OR GRANT NO. F 33657-67-C-0105 ✓ b. PROJECT NO. VELA T/6708 c. d.		8a. ORIGINATOR'S REPORT NUMBER(S)  —  8b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES  Distribution of this document is unlimited			
11. SUPPLEMENTARY NOTES  ARPA Order No. 624, Program Code No. 6F10		12. SPONSORING MILITARY ACTIVITY Advanced Research Projects Agency Department of Defense The Pentagon Washington, D. C. 20301	
13. ABSTRACT A bathymetric survey was conducted as a part of the Kurile Islands Experiment (Ocean-Bottom Seismograph Experiments, Contract No. F 33657-67-C-0105-P002). Since the primary efforts of the experiment were directed toward the Ocean-Bottom Seismograph and Explosive Program, the method used during the bathymetric survey was appropriate but not optimum. Bathymetric data were very good and were as reliable as navigation would permit. However, the profile coverage was generally too sparse. The conclusion is that observations of depth values, OBS-environmental relations and overall bathymetry are valid within navigational limits. ( )			

Unclassified  
Security Classification

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	Bathymetric Survey Kurile Islands Experiment OBS-environmental relations						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

Unclassified  
Security Classification